

Declaration of Performance

Product/DoP Ref: 033CPR13

Product-type: L11

Product intended to be used in walls and partitions

| Manufacturer | Notified Body |
|--|--|
| IG (Lintels) Ltd., Avondale Road, Cwmbran, Gwent, NP44 1XY | Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ |
| IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type L11 is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2003. | Ceram No. 1289, conducted determination of the product-type. The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2003. The AVCP for the product is system 3. |

| Essential Characteristics | | Lintel Length (mm) | | | hEN |
|---|---|---|-----------|-----------|----------------|
| | | 0600-1800 | 1950-2400 | 2550-3000 | |
| Load Bearing Capacity (kN) Total UDL | Figures shown are safe working loads | 16 | 20 | 22 | EN 845-2: 2003 |
| Deflection Under Load | | Less than Effective Span/325 at maximum safe working load | | | |
| Mass Per Unit Area | | NPD | | | |
| Water Absorption | | Zero | | | |
| Thermal Resistance (W/mk) | | 50 | | | |
| Resistance to Fire | | NPD (Contact IG Technical Department for information) | | | |
| Durability (against corrosion) | | L14 | | | |
| Durability (against freeze/thaw) | | Resistant | | | |
| Dangerous Substances | | None | | | |

Signed for on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

At: Cookstown

On: 30 / 06 / 2015

Signature: 