



Declaration of Performance

Revision 3

Product/DoP Ref: 001CPR2013

Product-type: L1/S 50

Product intended to be used in walls and partitions

Manufacturer	Notified Body
IG (Lintels) Ltd., Avondale Road, Cwmbram, Gwent, NP44 1XY	Technical and Test Institute for Construction Prague, Prosecká 811/76A, 190 00 Praha 9-Prosek, Czech Republic
IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type L1/S 50 is manufactured to the requirements of the Harmonised European Standard EN 845-2-2013+A1-2016.	TZUS No. 1020, conducted assessment of performance. The conformity of the product was determined as per the requirements stipulated in ZA.1 and ZA.2 of EN 845-2-2013+A1-2016. The AVCP for the product is system 3.

Essential Characteristics		Lintel Length (mm)										hEN
		0600-1200	1350-1500	1650-1800	1950-2100	2250-2400	2550-2700	2850-3000	3150-3600	3750-4050	4200-4800	
Load Bearing Capacity (kN) Load Ratio 3:1	Figures shown are safe working loads	12	14	19	21	21	26	27	27	26	27	EN 845-2-2013+A1-2016
Load Bearing Capacity (kN) Load Ratio 19:1		10	12	16	17	19	22	20	20	19	22	
Deflection Under Load	Less than Effective Span/325 at maximum safe working load											
Mass Per Unit Area	NPD											
Water Absorption	Zero											
Thermal Resistance (W/mk)	50 (steel), 0.039 (RNO)											
Resistance to Fire	NPD (Contact IG Technical Department for information)											
Durability (against corrosion)	L14 (Lintel), L16.1 (Thermal Break Plate)											
Durability (against freeze/thaw)	Resistant											
Dangerous Substances	None											

Signed on behalf of the manufacturer by:

Name: Derrick McFarland, Managing Director

At: Cookstown

On: 14 / 05 / 2021

Signature: